

ALBA ELETTRONICA SRL  
 VIA L DA VINCI 3  
 31021 MOGLIANO VENETO, TV ITALY

E203656

Type	Cond Width		Cond	SS/	Max		Max		Meets	C	
	Min	Edge			Area	Solder	Oper	Flame			UL796
	mm(in)	mm(in)	Thk	DS	Diam	Limits	Temp		Class	DSR	
<b>Multilayer printed wiring boards.</b>											
<b>M</b>	0.10 (0.004)	0.09 (0.004)	16.5 (0.65) Int:66	DS	76.2 (3.0)	260	10	105	V-0	All	3
<b>M1</b>	0.11 (0.004)	0.10 (0.004)	17 (0.67) Int:66	DS	25.5 (1.0)	288	10	105	V-0	All	4
<b>M2</b>	0.10 (0.004)	0.09 (0.004)	16.5 (0.65) Int:66	DS	76.2 (3.0)	288	10	130	V-0	All	3
<b>M3</b>	0.11 (0.004)	0.10 (0.004)	17 (0.67) Int:66	DS	25.5 (1.0)	288	10	130	V-0	All	4
<b>Single layer printed wiring boards.</b>											
<b>D</b>	0.10 (0.004)	0.09 (0.004)	16.5 (0.65)	DS	76.2 (3.0)	288	10	105	V-0	-	-
<b>D1</b>	0.10 (0.004)	0.09 (0.004)	16.5 (0.65)	DS	76.2 (3.0)	288	10	130	V-0	All	*
<b>D2</b>	0.10 (0.004)	0.09 (0.004)	16.5 (0.65)	DS	76.2 (3.0)	288	10	130	V-0	All	3
<b>D4</b>	0.10 (0.004)	0.09 (0.004)	16.5 (0.65)	DS	38.1 (1.5)	260	10	130	V-0	All	0
<b>D5</b>	0.10 (0.004)	0.09 (0.004)	16.5 (0.65)	DS	38.1 (1.5)	288	10	110	V-0	All	*

\* - CTI PLC may be marked on individual boards.

NOTE - A triangle is marked on those products within a given type designation that comply with direct support of current-carrying parts performance level requirements of UL 796. "All" is used to indicate that all base materials under that type designation comply with direct support of current-carrying parts performance level requirement of UL796.

 Marking: Company name or trademark  and type designation. May be followed by a suffix to denote factory identification.  
 Last Updated on 2006-06-30